



Performance Features:

Nominal Impedance: 50 Ω
 Frequency Range: DC-27GHz
 VSWR: DC-27GHz..... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI&PTFE



4th Floor, West Unit,
 Incubation Building 1
 Ganeshua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALUMINTECH.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALUMIN TECHNOLOGY.

DIRECTION OF VIEW

MINIATURE SYMBOLS:
 1. HOLE, ALL DIMENSIONS ALL CORNERS, SHARP EDGES, 0.45 R MAX
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1
 3. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING, UNLESS OTHERWISE SPECIFIED.

UNIT: mm

TITLE
 SMA Adapter

DWG NO. Z555510FS09A

LTR	DESCRIPTION	DATE	APPR.

DO NOT SCALE DRAWING

SIZE: A4_h SCALE: 2:1 REV: V2.0 SHEET: 1/1