



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-33GHz  
 VSWR: DC-33GHz..... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F Polished & Passivated  
 Center Contact: Beryllium Copper Gold Plated  
 Insulators: PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Ganqianhua Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALIVINTECH.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVIN TECHNOLOGY.

DIRECTION OF VIEW	UNIT
	mm
	mm

DRAWN	Shaohqing Du
CHECKED	Haimin Zhang
APPR.	Gang Cao

UNLESS OTHERWISE SPECIFIED:  
 1. HOLE, ALL DIMENSIONS, ALL CORNERS, SHARP EDGES, 0.40 R MAX.  
 2. DIMENSIONS ON CROWN CENTERS TO BE CONCENTRIC WITHIN 0.1  
 3. DIMENSIONS ON CROWN CENTERS TO BE CONCENTRIC WITHIN 0.1  
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISH: Ra

LTR	DESCRIPTION	DATE	APPR.

TITLE	3.5mm Adapter
DWG NO.	Z353500FY01

**OUTLINE DRAWING**

SIZE	A4_h	SCALE:	1	REV.	V2.0	SHEET	1/1
------	------	--------	---	------	------	-------	-----