



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-33GHz  
 VSWR: DC-33GHz.... 1.25:1 (Max)

**Materials/Finishes:**

Housing: SU303F  
 Polished & Passivated  
 Center Contact: Beryllium Copper  
 Gold Plated  
 Insulators:PEI

 4th Floor, West Unit, Incubation Building 1 Guanghua Lu, Nanjing TEL:025-84304950 FAX:025-84304959 WWW.ALLWINTEK.COM				DIRECTION OF VIEW 		UNIT mm		TITLE <b>3.5mm Adapter</b>			
<small>PROPRIETARY INFORMATION: THE INFORMATION WITHIN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALLWIN TECHNOLOGY.</small>				DRAWN Weihao Pan CHECKED Shaoqing Du APPR. Gang Cao		DWG NO. <b>Z353510W01</b>					
<small>UNLESS OTHERWISE SPECIFIED          1. REMOVE ALL BURRS, BREAK ALL CORNERS, SHARP EDGES 0.05 R MAX          2. LINEARITY TOLERANCES ±0.1, ANGLE TOLERANCES ±1°          3. DIAMETERS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1          4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHED ✓</small>				<b>OUTLINE DRAWING</b>							
LTR	DESCRIPTION	DATE	APPR.	DO NOT SCALE DRAWING				SIZE A4 h	SCALE 4:1	REV. V2.0	SHEET 1/1