



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-18GHz
 VSWR: DC-18GHz.... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganqianba Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALUMINTECH.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALUMIN TECHNOLOGY.



UNIT
 mm

TITLE
 APC7mm-N Adapter

DRAWN Kongtong Fang
 CHECKED Haijin Zhang
 APPR. Gang Cao

DWG NO.
 Z3334N0Z01

LTR	DESCRIPTION	DATE	APPR.

1. MAKE ALL DIMENSIONS ALL CORNERS SHARP UNLESS OTHERWISE SPECIFIED.
 2. DIMENSIONS ON CROWN CENERS TO BE CONCENTRIC WITHIN 0.1
 3. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES
 DO NOT SCALE DRAWING

SIZE A4_h SCALE: 1 REV. V1.1 SHEET 1/1

OUTLINE DRAWING