

Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-18GHz
 VSWR: DC-18GHz.... 1.15:1 (Max)

Materials/Finishes:


Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI

1 2



4th Floor, West Unit,
 Incubation Building 1
 Ganqian Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMENTER.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW	UNIT
	mm

DRAWN	Shaoping Du
CHECKED	Haimin Zhang
APPR.	Gang Cao

1. UNLESS OTHERWISE SPECIFIED, FINISHES SHALL BE AS SHOWN.
 2. DIMENSIONS ON CROWN CORNERS TO BE CONCENTRIC WITHIN 0.1
 3. ALL DIMENSIONS ARE AFTER PLATING, UNLESS OTHERWISE SPECIFIED.
 DO NOT SCALE DRAWING

TITLE	DWG NO.
APC7mm-N Adapter	Z3334N1Z01

OUTLINE DRAWING	
SIZE A4_h	SCALE
REV. V1.1	SHEET 1/1

5 6