



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-18GHz  
 VSWR: DC-18GHz... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F Polished & Passivated  
 Center Contact: Beryllium Copper Gold Plated  
 Insulators: PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Ganeshua Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALUMINTECH.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALUMIN TECHNOLOGY.



UNIT  
 mm

TITLE  
**N-2.92mm Adapter**

DRAWN: Shaoping Du  
 CHECKED: Haijin Zhang  
 APPR.: Gang Cao

DWG NO.  
**Z343610Z01**

LTR	DESCRIPTION	DATE	APPR.

1. DRAWING ALL DIMENSIONS UNLESS OTHERWISE SPECIFIED.  
 2. DIMENSIONS ON CROWN CENTERS TO BE CONSIDERED UNLESS NOTED.  
 3. DIMENSIONS ON CROWN CENTERS TO BE CONSIDERED WITHIN 0.1  
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES  
**DO NOT SCALE DRAWING**

OUTLINE DRAWING

1 2

5 6

SHEET 1/1