



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-18GHz
 VSWR: DC-18GHz... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganqunhua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMENTER.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.



UNIT
 mm

TITLE
N-2.4mm Adapter

DRAWN: Shaoping Du
 CHECKED: Haijin Zhang
 APPR.: Gang Cao

DWG NO.
Z343710Z01

LTR	DESCRIPTION	DATE	APPR.

1. UNLESS OTHERWISE SPECIFIED:
 1. HOLE, ALL DIMENSIONS ARE IN MILLIMETERS.
 2. DIMENSIONS ON CIRCULAR PARTS TO BE CONCENTRIC WITHIN 0.1.
 3. ALL DIMENSIONS ARE AFTER FINISHING. SURFACE FINISHES:
 DO NOT SCALE DRAWING

SIZE: A4_h SCALE: 4:1 REV: V2.0 SHEET: 1/1

OUTLINE DRAWING

1 2

5 6