



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-8GHz
 VSWR: DC-8GHz... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PTFE&PEI



4th Floor, West Unit,
 Incubation Building 1
 Guanghua Lu, NanJing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALIVINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVIN TECHNOLOGY.

DIRECTION OF VIEW



UNIT: mm

DRAWN: Shaoqing Du
 CHECKED: Haijin Zhang
 APPR.: Gang Cao

UNLESS OTHERWISE SPECIFIED:
 1. FINISH: ALL DIMS, BREAK ALL CORNERS, SHARP EDGES (0.05 R MAX)
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES

TITLE: N-BNC Adapter

DWG NO.: Z345210Z01

OUTLINE DRAWING

1	2	3	4	5	6
LTR	DESCRIPTION	DATE	APPR.	DO NOT SCALE DRAWING	SIZE: A4_h SCALE: 1 REV: V2.0 SHEET 1/1