



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-18GHz
 VSWR: DC-18GHz ... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI&PTFE



4th Floor, West Unit,
 Incubation Building 1
 Ganqianba Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALUMINTECH.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALUMIN TECHNOLOGY.

DIRECTION OF VIEW

UNIT
 mm

TITLE
N-SMA Adapter

DWG NO.
Z345500Z01

APPR.	Shaoqing Du
CHECKED	Haijin Zhang
APPR.	Gang Cao

1. UNLESS OTHERWISE SPECIFIED:
 1. HOLE, ALL DIMENSIONS ARE IN MILLIMETERS.
 2. DIMENSIONS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1
 3. DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES

DO NOT SCALE DRAWING

LTR	DESCRIPTION	DATE	APPR.

SIZE: A4_h SCALE: 1 REV: V1.1 SHEET: 1/1

1 2

5 6