



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-18GHz
 VSWR: DC-18GHz... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI&PTFE



4th Floor, West Unit,
 Incubation Building 1
 Ganqianba Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMTECH.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW

 DRAWN: Shaogqing Du
 CHECKED: Haijin Zhang
 APPR: Gang Cao

UNIT
 mm

TITLE
 N-SMA Adapter

DWG NO.
 Z345501Z01

LTR	DESCRIPTION	DATE	APPR.

DO NOT SCALE DRAWING

SIZE A4_h | **SCALE**: 1 | **REV.** V1.1 | **SHEET** 1/1

1 2

5 6