



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-33GHz
 VSWR: DC-33GHz... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganqunhua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMENTER.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW

 UNIT
 mm

DRAWN: Shaoping Du
 CHECKED: Haijin Zhang
 APPR: Gang Cao

1. MAKE ALL DIMENSIONS ALL CORNERS SHARP UNLESS OTHERWISE SPECIFIED.
 2. DIMENSIONS ON CROWN CENTERS TO BE CONSIDERED UNLESS OTHERWISE SPECIFIED.
 3. DIMENSIONS ON CROWN CENTERS TO BE CONSIDERED WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING, UNLESS OTHERWISE SPECIFIED.
 DO NOT SCALE DRAWING

TITLE
2.92mm – 3.5mm Adapter

DWG NO.
Z353600Z01

OUTLINE DRAWING

SIZE: A4_h SCALE: 1 REV: V1.1 SHEET: 1/1

LTR	DESCRIPTION	DATE	APPR.