



Performance Features:

Nominal Impedance: 50Ω
Frequency Range: DC-27GHz
VSWR: DC-27GHz..... 1.20:1 (Max)

Materials/Finishes:

Housing: SU303F
Center Contact: Beryllium Copper
Insulators:PTFE&PEI



4th Floor, West Unit,
Incubation Building 1
Ganghua Lu, Nanjing
TEL:025-84304950
FAX:025-84304959
WWW.ALWINTERK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.



UNIT
mm

DRAWN	Rongtong Fang
CHECKED	Haimin Zhang
APPR.	Gang Cao

1. REMOVE ALL DIMENSIONS SPECIFIED.
2. REMOVE ALL DIMENSIONS SPECIFIED.
3. DIMENSIONS ON CROWN CEMENTS TO BE CONCENTRIC WITHIN 0.1
4. ALL DIMENSIONS ARE AFTER PLATING. SURFACE FINISHED

LTR	DESCRIPTION	DATE	APPR.

TITLE
SMA Adapter

DWG NO.
K555510P01

OUTLINE DRAWING

SIZE	A4_h	SCALE:	1	REV.	V2.0	SHEET	1/1
------	------	--------	---	------	------	-------	-----