



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-40GHz
 VSWR: DC-40GHz..... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Guanghua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW: ALLWINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION WITH THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVIN TECHNOLOGY.



DIRECTION OF VIEW

UNIT
 mm

TITLE
2.92mm Connector

DRAWN	Xin Gong	DWG. NO.	D360S15F07
CHECKED	Haidin Zhang	SIZE	A4-h
APPR.	Gang Cao	SCALE	4:1

UNLESS OTHERWISE SPECIFIED:
 1. HOLE ALL DIMENSIONS, UNLESS SPECIFIED, ARE IN MILLIMETERS.
 2. DIMENSIONS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1.
 3. DIMENSIONS ON COMMON CENTERS TO BE CONCENTRIC WITHIN 0.1.
 4. ALL DIMENSIONS ARE AFTER FINISHING, SURFACE FINISHES.

DO NOT SCALE DRAWING

OUTLINE DRAWING
 REV. V2.0
 SHEET 1/1

1 2 3 4 5 6