



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-40GHz
 VSWR: DC-40GHz.... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganqunba Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION WITH THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW

 UNIT
 mm

DRAWN: Shaohong Du
 CHECKED: Haimin Zhang
 APPR. Gang Cao

1. REMOVE ALL DIMENSIONS UNLESS SPECIFIED.
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1
 3. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER MATING. SURFACE FINISHED.
 DO NOT SCALE DRAWING

TITLE
2.92mm Connector

DWG NO.
D361S09F04

OUTLINE DRAWING

LTR	DESCRIPTION	DATE	APPR.

SIZE: A4_h	SCALE: 4:1	REV. V2.0	SHEET 1/1
------------	------------	-----------	-----------