



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-40GHz  
 VSWR: DC-40GHz..... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F  
 Polished & Passivated  
 Center Contact: Beryllium Copper  
 Gold Plated  
 Insulators: PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Guanghua Ln, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW: ALLWINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION WITH THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALWIN TECHNOLOGY.



UNIT  
 mm

TITLE  
**2.92mm Connector**

DWG. NO.  
**D361S18F04**

**OUTLINE DRAWING**

LTR	DESCRIPTION	DATE	APPR.

DRAWN	Shaoqing Du	DWG. NO.	D361S18F04
CHECKED	Haimin Zhang	SIZE	A4-h
APPR.	Gang Cao	SCALE	4:1
		REV.	V2.0
		SHEET	1/1

1 2

5 6