



Performance Features:

Nominal Impedance: 50 Ω
 Frequency Range: DC-50GHz
 VSWR: DC-50GHz.... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganabua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW: ALIVINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION WITH THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVIN TECHNOLOGY.

DIRECTION OF VIEW

ISO 128:2001

UNIT
mm

TITLE
2.4mm Connector

DRAWN Shaoping Du
CHECKED Gang Cao
APPR. Donald Wu

DWG NO.
D370S09F01

LTR	DESCRIPTION	DATE	APPR.

DO NOT SCALE DRAWING

1. UNLESS OTHERWISE SPECIFIED, FINISHES ARE TO BE AS SHOWN.
 2. DIMENSIONS ON CROWN CENTERS TO BE CONSIDERED UNLESS NOTED OTHERWISE.
 3. DIMENSIONS ON CROWN CENTERS TO BE CONSIDERED WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER MATING, SURFACE FINISHED.

SIZE A4-h **SCALE** A:1 **REV.** V2.0 **SHEET** 1/1