



Performance Features:

Nominal Impedance: 50 Ω
 Frequency Range: DC-50GHz
 VSWR: DC-50GHz.... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganabahu Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALIVINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVIN TECHNOLOGY.

DIRECTION OF VIEW	UNIT
	mm
	mm

DRAWN	Shaogqing Du
CHECKED	Gang Cao
APPR.	Donald Wu

1. DRAWN, ALL DIMENSIONS, UNLESS OTHERWISE SPECIFIED.
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1
 3. DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES

LTR	DESCRIPTION	DATE	APPR.

TITLE
2.4mm Connector

DWG NO.
D370S20F01

OUTLINE DRAWING