



Performance Features:

Nominal Impedance: 50 Ω
 Frequency Range: DC-50GHz
 VSWR: DC-50GHz.... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganabua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW

ISO Symbols for First Angle Projection:

- Front View:
- Top View:

UNIT
mm

TITLE
2.4mm Connector

DRAWN Shaoping Du
CHECKED Haijin Zhang
APPR. Gang Cao

DWG NO.
D370S20F02

LTR	DESCRIPTION	DATE	APPR.

DO NOT SCALE DRAWING

1. UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS.
 2. DIMENSIONS ON CROWN CENTERS TO BE CONSIDERED WITHIN 0.1.
 3. DIMENSIONS ON CROWN CENTERS TO BE CONSIDERED WITHIN 0.1.
 4. ALL DIMENSIONS ARE AFTER MATING, SURFACE FINISHED.

OUTLINE DRAWING

SIZE: A4-h SCALE: 4:1 REV: V2.0 SHEET 1/1