



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-50GHz  
 VSWR: DC-50GHz..... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F  
 Polished & Passivated  
 Center Contact: Beryllium Copper  
 Gold Plated  
 Insulators: PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Guanghua Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW: ALLWINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION WITH THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVIN TECHNOLOGY.



DIRECTION OF VIEW  
 UNIT  
 mm

TITLE  
**2.4mm Connector**

DWG. NO.  
**D370S15F06**

**OUTLINE DRAWING**

LTR	DESCRIPTION	DATE	APPR.

1. REMOVE ALL DIMENSIONS, ALL DIMENSIONS SHOWN HEREIN ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.  
 2. DIMENSIONS ON DIMENSION LINES TO BE CONSIDERED UNLESS OTHERWISE SPECIFIED.  
 3. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED UNLESS OTHERWISE SPECIFIED.  
 4. ALL DIMENSIONS ARE AFTER FINISHING SERVICE FINISHED.

DO NOT SCALE DRAWING