



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-27GHz
 VSWR: DC-50GHz... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PBI



4th Floor, West Unit,
 Invention Building 1
 Guanghua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALIVINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVIN TECHNOLOGY.

DIRECTION OF VIEW		UNIT	mm
DRAWN	Xin Gong	CHECKED	Haimin Zhang
APPR.	Gang Cao		

TITLE	2.4mm Connector
DWG NO.	D370S12Y01

LTR	DESCRIPTION	DATE	APPR.

DO NOT SCALE DRAWING	SIZE A4_h	SCALE: 4:1	REV. V2.0	SHEET 1/1
----------------------	-----------	------------	-----------	-----------

1 2

5 6