



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-50GHz
 VSWR: DC-50GHz.... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganaguan Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALIVMENTER.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVM TECHNOLOGY.

DIRECTION OF VIEW	UNIT
	mm

DRAWN	Shaoping Du
CHECKED	Hailin Zhang
APPR.	Gang Cao

1. DRAW ALL DIMENSIONS UNLESS SPECIFIED.
 2. DIMENSIONS ON CROWN CENTERS TO BE CONSIDERED UNLESS NOTED OTHERWISE.
 3. DIMENSIONS ON CROWN CENTERS TO BE CONSIDERED WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES.

LTR	DESCRIPTION	DATE	APPR.

2.4mm Connector

DWG NO. D371S09F05

OUTLINE DRAWING

SIZE	A4_h	SCALE:	1	REV.	V2.0	SHEET	1/1
------	------	--------	---	------	------	-------	-----