



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-50GHz
 VSWR: DC-50GHz.... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganaguan Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALIVMENTER.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVM TECHNOLOGY.

DIRECTION OF VIEW

UNIT
mm

TITLE
2.4mm Connector

DRAWN Shaogang Du
CHECKED Haijin Zhang
APPR. Gang Cao

DWG NO.
D371S12F05

1. DRAW ALL DIMENSIONS UNLESS OTHERWISE SPECIFIED.
 2. DIMENSIONS ON CIRCULAR PARTS TO BE CONCENTRIC UNLESS OTHERWISE SPECIFIED.
 3. DIMENSIONS ON CIRCULAR PARTS TO BE CONCENTRIC WITHIN 0.1.
 4. ALL DIMENSIONS ARE AFTER PLATING, SURFACE FINISHES.

DO NOT SCALE DRAWING

LTR DESCRIPTION DATE APPR.

SIZE A4_h **SCALE**: 1 **REV.** V2.0 **SHEET** 1/1

1 2

5 6