



Performance Features:

Nominal Impedance: 50 Ω
 Frequency Range: DC-65GHz
 VSWR: DC-65GHz.... 1.25:1 (Max)

Materials/Finishes:

Housing: SU303F
 Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganqunhua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALIVMTECH.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVM TECHNOLOGY.

DIRECTION OF VIEW

FRONT VIEW:

TOP VIEW:

UNIT
mm

TITLE
1.85mm Connector

DWG NO.
D380S09F01

LTR	DESCRIPTION	DATE	APPR.

DO NOT SCALE DRAWING

SIZE A4_h | **SCALE** 4:1 | **REV.** V2.0 | **SHEET** 1/1

DRAWN Hongtong Fang
CHECKED Haijin Zhang
APPR. Gang Cao

INVESTIGATOR'S SPECIFICATION:
 1. FORM: ALL DIMENSIONS, ALL CORNERS, SHARP EDGES 0.40 R MAX
 2. FINISHES: ALL DIMENSIONS TO BE CONFORMANCE WITHIN 0.1
 3. DIMENSIONS ON CROWN CENTERS TO BE CONFORMANCE WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING. SURFACE FINISHED

OUTLINE DRAWING