



SOCKET TO ACCEPT $\phi 0.30(.012)$
PIN $2(.079)$ MAX DEPTH

Performance Features:

Nominal Impedance: 50 Ω
 Frequency Range: DC-65GHz
 VSWR: DC-65GHz.... 1.25:1 (Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganaguda Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION WITH THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW

 UNIT
 mm

DRAWN: Hongtong Fang
 CHECKED: Min Hai Zhang
 APPR.: Gang Cao

1. REMOVE ALL DIMENSIONS, ALL CORNERS, SHARP EDGES, 0.40 R MAX
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1
 3. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER MATING, SURFACE FINISHED
 DO NOT SCALE DRAWING

TITLE
1.85mm Connector

DWG NO.
D380S12Y01

OUTLINE DRAWING

SIZE: A4_h SCALE: 4:1 REV: V2.0 SHEET 1/1