



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-65GHz
 VSWR: DC-65GHz.... 1.25:1 (Max)

Materials/Finishes:

Housing: SU303F
 Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganaguan Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALIVMENTER.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVM TECHNOLOGY.



UNIT
 mm

TITLE
1.85mm Connector

DRAWN: Shaogqing Du
 CHECKED: Haijin Zhang
 APPR.: Gang Cao

DWG NO.
D381S09F05

| LTR | DESCRIPTION | DATE | APPR. |
|-----|-------------|------|-------|
| | | | |
| | | | |
| | | | |

DO NOT SCALE DRAWING

SIZE: A4_h SCALE: 4:1 REV: V2.0 SHEET: 1/1

OUTLINE DRAWING