



**Performance Features:**

Nominal Impedance: 50Ω  
 Frequency Range: DC-18GHz  
 VSWR: DC-18GHz.... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F Polished & Passivated  
 Center Contact: Beryllium Copper Gold Plated  
 Insulators: PTFE&PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Ganabua Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALIVINTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVIN TECHNOLOGY.

DIRECTION OF VIEW  
  
 UNIT  
 mm

DRAWN: Shaoqing Du  
 CHECKED: Haijin Zhang  
 APPR: Gang Cao

TITLE  
**N Connector**

DWG NO.  
**D340S18F09**

**OUTLINE DRAWING**

LTR DESCRIPTION DATE APPR.

DO NOT SCALE DRAWING

SIZE A4\_h SCALE:3:1 REV. V2.0 SHEET1/1