



**Performance Features:**

Nominal Impedance: 50 $\Omega$   
 Frequency Range: DC-18GHz  
 VSWR: DC-18GHz.... 1.15:1 (Max)

**Materials/Finishes:**

Housing: SU303F  
 Polished & Passivated  
 Center Contact: Beryllium Copper  
 Gold Plated  
 Insulators: PTFE&PEI



4th Floor, West Unit,  
 Incubation Building 1  
 Ganaguan Lu, Nanjing  
 TEL: 025-84304950  
 FAX: 025-84304959  
 WWW.ALVIMTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

DIRECTION OF VIEW

UNIT  
 mm

TITLE  
 N Connector

DRAWN: Shaohong Du  
 CHECKED: Haijin Zhang  
 APPR: Gang Cao

DWG NO.  
 D340S20F01

LTR	DESCRIPTION	DATE	APPR.

DO NOT SCALE DRAWING

SIZE: A4\_h SCALE: 1:1 REV: V2.0 SHEET 1/1