



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-18GHz
 VSWR: DC-18GHz..... 1.15:1 (Max)

Materials/Finishes:

Housing: SU303F
 Polished & Passivated
 Center Contact: Beryllium Copper
 Gold Plated
 Insulators: PTFE&PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganqunhua Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALVIMENTER.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALVIM TECHNOLOGY.

| DIRECTION OF VIEW | UNIT |
|-------------------|------|
| | mm |

| | |
|---------|--------------|
| DRAWN | Shaoqing Du |
| CHECKED | Haimin Zhang |
| APPR. | Gang Cao |

| | |
|---------|----------------|
| TITLE | TNCA Connector |
| DWG NO. | D540S36F09 |

| LTR | DESCRIPTION | DATE | APPR. |
|-----|-------------|------|-------|
| | | | |
| | | | |
| | | | |

| | | | | |
|----------------------|-----------|----------|-----------|-----------|
| DO NOT SCALE DRAWING | SIZE A4_h | SCALE: 1 | REV. V2.0 | SHEET 1/1 |
|----------------------|-----------|----------|-----------|-----------|

