



Performance Features:

Nominal Impedance: 50Ω
 Frequency Range: DC-27GHz
 VSWR: DC-40GHz.... 1.20:1 (Max)

Materials/Finishes:

Housing: SU303F Polished & Passivated
 Center Contact: Beryllium Copper Gold Plated
 Insulators: PTFE&PEI



4th Floor, West Unit,
 Incubation Building 1
 Ganqianba Lu, Nanjing
 TEL: 025-84304950
 FAX: 025-84304959
 WWW.ALIVMTEK.COM

PROPRIETARY INFORMATION. THE INFORMATION IN THIS DRAWING IS PROPRIETARY AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN PERMISSION FROM ALIVM TECHNOLOGY.

DIRECTION OF VIEW	UNIT
	mm
	mm

DRAWN	Xin Gong
CHECKED	Haidin Zhang
APPR.	Gang Cao

1. DRAWING ALL DIMENSIONS UNLESS OTHERWISE SPECIFIED.
 2. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1
 3. DIMENSIONS ON COMMON CENTERS TO BE CONSIDERED WITHIN 0.1
 4. ALL DIMENSIONS ARE AFTER PLATING. SOURCE FINISHED.

LTR	DESCRIPTION	DATE	APPR.

TITLE
SSMA Connector

DWG NO.
D571S12F08

OUTLINE DRAWING

1	2	3	4	5	6

SIZE	A4_h	SCALE:	1	REV.	V2.0	SHEET	1/1
------	------	--------	---	------	------	-------	-----